

MODEL	<u>OAC1211</u>	<u>OAC1811</u>	<u>OAC2412</u>	<u>OAC3612</u>	<u>OAC3632</u>	<u>OAC6012</u>	<u>OAC6032</u>
Cooling Capacity <sup>1</sup>	12,700	18,010	24,020	36,050	36,050	60,050	60,050
Voltage	115/60/1 or 208/230/1		208/230/1		208/230/3	208/230/1	208/230/3
Cooling Amps <sup>2</sup>	12.0/7.0	15.5/7.8	12.3	22.5	14	34.0	25.0
Cooling Watts <sup>2</sup>	1256	1590	2200	3360	3360	5900	5900
E.E.R. <sup>5</sup>	10.1	11.3	10.9	10.7	10.7	10.1	10.1
In Rush Current (AMPS)	92.8	114.2	79	128.8	111.8	198.0	134.2
Fuse/Breaker(Amps) <sup>4</sup>	20	20	20	30	20	50	40
Plug Type	5-20P	5-20P	6-20P	6-30P	6-30P	6-50P	L15-30P
Compressor HP	1	1 1/2	2	3	3	5	5
Compressor RLA	9.3	11.4	8.3	17.9	11.4	28.0	20.0
Compressor LRA	58	65	49	88	77	169	123
Evaporator CFM <sup>3</sup>	400	600	810	1310	1310	2200	2200
Evap Motor HP	1/15	1/5	1/3	1/2	1/2	1	1
Evap Motor Watts	200	210	350	375	375	550	550
Condenser CFM <sup>3</sup>	580	930	1010	1390	1390	2900	2900
Condenser Motor HP	1/8	1/3	1/2	3/4	3/4	1	1
Condenser Motor Watts	280	450	330	460	460	750	750
Condensate Pump Head 20 Feet	Pump Optional on these units					Pump Standard on 5-Ton	
Sound Level <sup>6</sup>	54	60	65	69		78	
R-22 Charge Oz.	29	42	40	45		68	
Height with Casters	31 1/2	37 1/2	37 1/2	47		52 1/4	
Height without Casters	28 1/2	34 1/2		42 1/4		46 1/2	
Width	20 1/8	24 1/4		28 1/4			
Depth	22 5/8	24 3/4		31		46	
Net Weight	160	215	225	335	335	540	540

Shipping Weight	180	245	255	365	365	590	590
Shipping Volume	15	32	32	36	36	44	44

1. Cooling Capacity @ 80&deg;F DB/67&deg;F W.B. Indoor 95&deg;F DB/75&deg;FW.B. Outdoor
2. Amps & Watts at 208 Volts
3. CFM with free discharge
4. Time delay fuses/circuit breakers are recommended
5. EER determined with condenser discharge air ducted into another area on high fan speed
6. Sound pressure, dB at 5 feet, commercial configuration

**All units available in 220/50 cycle**

Electrical ratings per U.L. 484 at 95&deg;F DB/75&deg;WB on high fan speed

Specifications subject to change without notice.

March 30, 2000